


Features

- 68V/70A,
 $R_{DS(ON)} = 6.5\text{m}\Omega$ (typ.) @ $V_{GS} = 10\text{V}$
- 100% UIS + R_g Tested
- Reliable and Rugged
- Lead Free and Green Devices Available
(RoHS Compliant)


Applications

- Synchronous Rectification.
- Power Management in Inverter Systems.

Pin Description



Top View of TO-263



N-Channel MOSFET

Absolute Maximum Ratings ($T_A = 25^\circ\text{C}$ Unless Otherwise Noted)

Symbol	Parameter		Rating	Unit
Common Ratings				
V _{DSS}	Drain-Source Voltage		68	V
V _{GSS}	Gate-Source Voltage		±25	
T _J	Maximum Junction Temperature		175	°C
T _{STG}	Storage Temperature Range		-55 to 175	
I _S	Diode Continuous Forward Current	T _C =25°C	70	A
Mounted on Large Heat Sink				
I _{DP}	Pulse Drain Current Tested	T _C =25°C	210	A
I _D	Continuous Drain Current	T _C =25°C	70	A
		T _C =100°C	53	
P _D	Maximum Power Dissipation	T _C =25°C	150	W
		T _C =100°C	75	
R _{θJC}	Thermal Resistance-Junction to Case		1	°C/W
R _{θJA}	Thermal Resistance-Junction to Ambient		62.5	
I _{AS} ^b	Avalanche Current, Single pulse	L=0.5mH	40	A
E _{AS} ^b	Avalanche Energy, Single pulse	L=0.5mH	400	mJ

Note * : Bonding wire limitation current is 80A.

Note a : Pulse width limited by max. junction temperature.

Note b : UIS tested and pulse width limited by maximum junction temperature 150°C (initial temperature $T_J=25^\circ\text{C}$).





Electrical Characteristics (T_A = 25°C Unless Otherwise Noted)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
Static Characteristics						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _{DS} =250μA	68	-	-	V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =54V, V _{GS} =0V	-	-	1	μA
		T _J =85°C	-	-	30	
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _{DS} =250μA	2	3	4	V
I _{GSS}	Gate Leakage Current	V _{GS} =±25V, V _{DS} =0V	-	-	±100	nA
R _{DS(ON)} ^c	Drain-Source On-state Resistance	V _{GS} =10V, I _{DS} =40A	-	6.5	8.0	mΩ
Diode Characteristics						
V _{SD} ^c	Diode Forward Voltage	I _{SD} =20A, V _{GS} =0V	-	0.8	1.3	V
t _{rr}	Reverse Recovery Time	I _{SD} =40A, dI _{SD} /dt=100A/μs	-	30	-	ns
Q _{rr}	Reverse Recovery Charge		-	32	-	nC
Dynamic Characteristics ^d						
R _G	Gate Resistance	V _{GS} =0V, V _{DS} =0V, f=1MHz	-	1	-	Ω
C _{iss}	Input Capacitance	V _{GS} =0V, V _{DS} =30V, Frequency=1.0MHz	-	3985	4360	pF
C _{oss}	Output Capacitance		-	265	-	
C _{rss}	Reverse Transfer Capacitance		-	185	-	
t _{d(ON)}	Turn-on Delay Time	V _{DD} =30V, R _L =30Ω, I _{DS} =1A, V _{GEN} =10V, R _G =6Ω	-	16	29	ns
t _r	Turn-on Rise Time		-	10	18	
t _{d(OFF)}	Turn-off Delay Time		-	40	72	
t _f	Turn-off Fall Time		-	35	63	
Gate Charge Characteristics ^d						
Q _g	Total Gate Charge	V _{DS} =30V, V _{GS} =10V, I _{DS} =40A	-	46	65	nC
Q _{gs}	Gate-Source Charge		-	16	-	
Q _{gd}	Gate-Drain Charge		-	12	-	





Note c : Pulse test ; pulse width≤300μs, duty cycle≤2%.

Note d : Guaranteed by design, not subject to production testing.





Typical Operating Characteristics





Typical Operating Characteristics (Cont.)

Output Characteristics

Drain-Source On Resistance

Gate-Source On Resistance

Gate Threshold Voltage




Typical Operating Characteristics (Cont.)

Drain-Source On Resistance

Source-Drain Diode Forward

Capacitance

Gate Charge


Avalanche Test Circuit and Waveforms




Switching Time Test Circuit and Waveforms



Package Information


TO-263



SYMBOL	TO-263			
	MILLIMETERS		INCHES	
	MIN.	MAX.	MIN.	MAX.
A	4.06	4.83	0.160	0.190
A1	0.00	0.25	0.000	0.010
b	0.51	0.99	0.020	0.039
b2	1.14	1.78	0.045	0.070
c	0.38	0.74	0.015	0.029
c2	1.14	1.65	0.045	0.065
D	8.38	9.65	0.330	0.380
D1	6.00	9.00	0.236	0.354
E	9.65	11.43	0.380	0.450
E1	6.22	9.00	0.245	0.354
e	2.54 BSC		0.100 BSC	
H	14.61	15.88	0.575	0.625
L	1.78	2.79	0.070	0.110
L1	-	1.68	-	0.066
L2	-	1.78	-	0.070
θ	0°	8°	0°	8°

Note : Follow JEDEC TO-263 AB.

RECOMMENDED LAND PATTERN



UNIT: mm