


Features

- 30V/-180A
 $R_{DS(ON)} = 1.9m\Omega (typ.) @ V_{GS} = -10V$
 $R_{DS(ON)} = 2.7m\Omega (typ.) @ V_{GS} = -4.5V$
- 100% UIS + R_g Tested
- Reliable and Rugged
- Lead Free and Green Devices Available (RoHS Compliant)


Applications

- Power Management in Notebook Computer, Portable Equipment and Battery Powered Systems.

Pin Description



DFN5x6A-8_EP



P-Channel MOSFET

Absolute Maximum Ratings ($T_A=25^{\circ}\text{C}$ Unless Otherwise Noted)

Symbol	Parameter		Rating	Unit
Common Ratings				
V _{DSS}	Drain-Source Voltage		-30	V
V _{GSS}	Gate-Source Voltage		±25	
T _J	Maximum Junction Temperature		150	°C
T _{STG}	Storage Temperature Range		-55 to 150	
I _S	Diode Continuous Forward Current	T _C =25°C	-180	A
I _D	Continuous Drain Current	T _C =25°C	-180	A
		T _C =100°C	-135	
I _{DM} ^a	Pulsed Drain Current	T _C =25°C	-540	
P _D	Maximum Power Dissipation	T _C =25°C	178	W
		T _C =100°C	71	
R _{θJC}	Thermal Resistance-Junction to Case		0.7	°C/W
R _{θJA} ^c	Thermal Resistance-Junction to Ambient		55	°C/W
I _{AS} ^b	Avalanche Current, Single pulse	L=0.5mH	-60	A
E _{AS} ^b	Avalanche Energy, Single pulse	L=0.5mH	900	mJ

Note * : Current limited by bonding wire.

Note a : Pulse width limited by maximum junction temperature and package.

Note b : UIS tested and pulse width limited by maximum junction temperature (initial temperature $T_J=25^{\circ}\text{C}$).

Note c : Surface Mounted on 1in^2 pad area.

Electrical Characteristics ($T_A = 25^\circ\text{C}$ unless otherwise noted)


Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
Static Characteristics						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _{DS} =-250μA	-30	-	-	V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =-24V, V _{GS} =0V T _J =85°C	-	-	-1	μA
			-	-	-30	
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _{DS} =-250μA	-1.0	-1.8	-2.5	V
I _{GSS}	Gate Leakage Current	V _{GS} =±25V, V _{DS} =0V	-	-	±100	nA
R _{DS(ON)} ^d	Drain-Source On-state Resistance	V _{GS} =-10V, I _{DS} =-50A	-	1.9	2.5	mΩ
		V _{GS} =-4.5V, I _{DS} =-30A	-	2.7	3.6	
Diode Characteristics						
V _{SD} ^d	Diode Forward Voltage	I _{SD} =-36A, V _{GS} =0V	-	-0.8	-1.1	V
t _{rr}	Reverse Recovery Time	I _{SD} =-50A, dI _{SD} /dt=100A/μs	-	39	-	ns
Q _{rr}	Reverse Recovery Charge		-	28	-	nC
Dynamic Characteristics ^e						
R _G	Gate Resistance	V _{GS} =0V, V _{DS} =0V, F=1MHz	-	3	-	Ω
C _{iss}	Input Capacitance	V _{GS} =0V, V _{DS} =-15V, Frequency=1.0MHz	-	8100	10500	pF
C _{oss}	Output Capacitance		-	1020	-	
C _{rss}	Reverse Transfer Capacitance		-	640	-	
t _{d(ON)}	Turn-on Delay Time	V _{DD} =-15V, R _L =15Ω, I _{DS} =-1A, V _{GEN} =-10V, R _G =6Ω	-	22	40	ns
t _r	Turn-on Rise Time		-	22	40	
t _{d(OFF)}	Turn-off Delay Time		-	166	299	
t _f	Turn-off Fall Time		-	88	158	
Gate Charge Characteristics ^e						
Q _g	Total Gate Charge	V _{DS} =-15V, V _{GS} =-10V, I _{DS} =-50A	-	120	168	nC
Q _g	Total Gate Charge	V _{DS} =-15V, V _{GS} =-4.5V, I _{DS} =-50A	-	56	-	
Q _{gs}	Gate-Source Charge		-	30	-	
Q _{gd}	Gate-Drain Charge		-	23	-	

Note d : Pulse test ; pulse width $\leq 300\mu s$, duty cycle $\leq 2\%$.


Note e : Guaranteed by design, not subject to production testing.

Typical Operating Characteristics


Power Dissipation




Drain Current







Safe Operation Area



Thermal Transient Impedance




Typical Operating Characteristics(Cont.)


Gate-Source On Resistance

Gate Threshold Voltage

Output Characteristics

Drain-Source On Resistance


Typical Operating Characteristics(Cont.)


Capacitance




Gate Charge





Drain-Source On Resistance





Source-Drain Diode Forward




Avalanche Test Circuit and Waveforms



Switching Time Test Circuit and Waveforms




Package Information

DFN5x6-8


SYMBOL	DFN5x6-8			
	MILLIMETERS		INCHES	
	MIN.	MAX.	MIN.	MAX.
A	0.90	1.20	0.035	0.047
B	0.3	0.51	0.012	0.020
C	0.19	0.25	0.007	0.010
D	4.80	5.30	0.189	0.209
D1	4.00	4.40	0.157	0.173
E	5.90	6.20	0.232	0.244
E1	5.50	5.80	0.217	0.228
e	1.27 BSC		0.050 BSC	
F	0.05	0.30	0.002	0.012
F1	0.35	0.75	0.014	0.030
G	0.05	0.30	0.002	0.012
G1	0.35	0.75	0.014	0.030
H	3.34	3.9	0.131	0.154
K	0.762	-	0.03	-

RECOMMENDED LAND PATTERN



UNIT: mm

Note : 1.Dimension D, D1,D2 and E1 do not include mold flash or protrusions.
Mold flash or protrusions shall not exceed 10 mil.