


Features

- 40V/80A,
 $R_{DS(ON)} = 4.2m\Omega(\text{typ.}) @ V_{GS} = 10V$
 $R_{DS(ON)} = 5.2m\Omega(\text{typ.}) @ V_{GS} = 4.5V$
- 100% UIS + R_g Tested
- Reliable and Rugged
- Lead Free and Green Devices Available (RoHS Compliant)


Applications

- SMPS Synchronous Rectification.
- Load Switch.
- DC-DC Conversion.

Pin Description



PDFN5*6-8L



N-Channel MOSFET

Absolute Maximum Ratings (T_A = 25°C Unless Otherwise Noted)

Symbol	Parameter		Rating	Unit
Common Ratings				
V _{DSS}	Drain-Source Voltage		40	V
V _{GSS}	Gate-Source Voltage		±20	
T _J	Maximum Junction Temperature		150	°C
T _{STG}	Storage Temperature Range		-55 to 150	
I _S	Diode Continuous Forward Current	T _C =25°C	80	A
I _D ^a	Continuous Drain Current	T _C =25°C	80	
		T _C =100°C	60	
I _{DM} ^b	Pulsed Drain Current	T _C =25°C	300	
P _D	Maximum Power Dissipation	T _C =25°C	54	W
		T _C =100°C	22	
R _{θJC}	Thermal Resistance-Junction to Case	Steady State	2.3	°C/W
R _{θJA} ^c	Thermal Resistance-Junction to Ambient	t ≤ 10s	17	°C/W
		Steady State	50	
I _{AS} ^d	Avalanche Current, Single pulse	L=0.1mH	50	A
E _{AS} ^d	Avalanche Energy, Single pulse	L=0.1mH	125	mJ

Note a : Max. continue current is limited by bonding wire.

Note b : Pulse width is limited by max. junction temperature.

Note c : Surface mounted on 1in2 pad area, steady state t=999s.

Note d : UIS tested and pulse width limited by maximum junction temperature 150°C (initial temperature T_J=25°C).





Electrical Characteristics (T_A = 25°C unless otherwise noted)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
Static Characteristics						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _{DS} =250μA	40	-	-	V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =32V, V _{GS} =0V T _J =85°C	-	-	1 30	μA
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _{DS} =250μA	1.3	1.7	2.5	V
I _{GSS}	Gate Leakage Current	V _{GS} =±20V, V _{DS} =0V	-	-	±100	nA
R _{DS(ON)} ^e	Drain-Source On-state Resistance	V _{GS} =10V, I _{DS} =40A V _{GS} =4.5V, I _{DS} =35A	-	4.2 5.2	5.5 6.5	mΩ
G _{fs}	Forward Transconductance	V _{DS} =5V, I _{DS} =20A	-	31	-	S
Diode Characteristics						
V _{SD} ^e	Diode Forward Voltage	I _{SD} =20A, V _{GS} =0V	-	0.75	1.1	V
t _{rr}	Reverse Recovery Time	I _{SD} =20A, dI _{SD} /dt=100A/μs	-	28	-	ns
t _a	Charge Time		-	17	-	
t _b	Discharge Time		-	12	-	
Q _{rr}	Reverse Recovery Charge		-	20	-	nC
Dynamic Characteristics ^f						
R _G	Gate Resistance	V _{GS} =0V, V _{DS} =0V, F=1MHz	-	1	2	Ω
C _{iss}	Input Capacitance	V _{GS} =0V, V _{DS} =20V, Frequency=1.0MHz	-	1622	2039	pF
C _{oss}	Output Capacitance		-	1035	-	
C _{rss}	Reverse Transfer Capacitance		-	58	-	
t _{d(ON)}	Turn-on Delay Time	V _{DD} =20V, R _L =20Ω, I _{DS} =1A, V _{GEN} =10V, R _G =6Ω	-	14.3	26	ns
t _r	Turn-on Rise Time		-	7.7	14	
t _{d(OFF)}	Turn-off Delay Time		-	32.6	59	
t _f	Turn-off Fall Time		-	26.6	48	
Gate Charge Characteristics ^f						
Q _g	Total Gate Charge	V _{DS} =20V, V _{GS} =10V, I _{DS} =20A	-	24.8	34.7	nC
Q _g	Total Gate Charge	V _{DS} =20V, V _{GS} =4.5V, I _{DS} =20A	-	11.5	-	
Q _{gth}	Threshold Gate Charge		-	3	-	
Q _{gs}	Gate-Source Charge		-	5.2	-	
Q _{gd}	Gate-Drain Charge		-	2.6	-	

Note e : Pulse test ; pulse width≤300μs, duty cycle≤2%.


Note f : Guaranteed by design, not subject to production testing.

Typical Operating Characteristics




Typical Operating Characteristics (Cont.)


Capacitance




Gate Charge







Output Characteristics





Drain-Source On Resistance





Typical Operating Characteristics (Cont.)



Avalanche Test Circuit and Waveforms




Switching Time Test Circuit and Waveforms



Package Information


PDFN5*6-8L



SYMBOL	PDFN5*6-8L			
	MILLIMETERS		INCHES	
	MIN.	MAX.	MIN.	MAX.
A	0.90	1.20	0.035	0.047
B	0.3	0.51	0.012	0.020
C	0.19	0.25	0.007	0.010
D	4.80	5.30	0.189	0.209
D1	4.00	4.40	0.157	0.173
E	5.90	6.20	0.232	0.244
E1	5.50	5.80	0.217	0.228
e	1.27 BSC		0.050 BSC	
F	0.05	0.30	0.002	0.012
F1	0.35	0.75	0.014	0.030
G	0.05	0.30	0.002	0.012
G1	0.35	0.75	0.014	0.030
H	3.34	3.9	0.131	0.154
K	0.762	-	0.03	-

Note : 1.Dimension D, D1,D2 and E1 do not include mold flash or protrusions.
Mold flash or protrusions shall not exceed 10 mil.

RECOMMENDED LAND PATTERN



UNIT: mm